

Visual Indicator Enclosure



The Visual Indicator Enclosure is weatherproof, allowing a loop-powered visual indicator to be installed outside and in high moisture environments such as swimming pools. The enclosure is supplied with a mounting bracket to accept an XPERT 7 Mounting Base.

Protects against water ingress

Allows visual indicators to be used outdoors

Accepts MiniDisc remote indicator

IP67 rated

29600-318
Visual Indicator Enclosure

DIN-Rail Interface Enclosures



DIN-Rail Interface Enclosures are available in two sizes and can be used for housing Intrinsically Safe (I.S.) barriers or DIN-Rail mounted interfaces. A multi-purpose label that features a section for use with I.S. systems is supplied. For non-I.S. systems, the part referring to I.S. can simply be removed.

Allows multiple interfaces to be housed together

IP67 rated

29600-239
DIN-Rail Interface Enclosure (4 units)

29600-240
DIN-Rail Interface Enclosure (10 units)

Series 90 to XP95 Base Adaptor



The Series 90 to XP95 Base Adaptor is designed to allow XP95 detectors to be fitted to an existing Series 90 base. The adaptor eliminates the need to rewire an existing Apollo intelligent system.

Allows an existing range to be updated with ease

Eliminates the need for re-wiring

45681-238
Series 90 to XP95 Base Adaptor

Series 65 to Orbis Base Adaptor



The Series 65 to Orbis Base Adaptor is designed to allow Orbis detectors to be fitted to an existing Series 60 or Series 65 base. The adaptor eliminates the need to rewire an existing Apollo conventional system.

Allows an existing range to be updated with ease

Eliminates the need for re-wiring

ORB-BA-10008-APO
Series 65 to Orbis Base Adaptor