

Discovery Manual Call Point



A seven-segment DIL switch enables addressing of each call point at commissioning stage. When operated, the manual call point interrupts the polling cycle for a fast response. Bi-coloured LEDs indicate isolate and normal conditions.

Flashing LED option to indicate polling (Discovery systems only)

'Plug and Play' terminal connections for fast wiring

Continuity link for wiring test before commissioning

Reports an alarm in under 0.2 seconds

Resettable element

58100-910
Discovery Manual Call Point

58100-908
Discovery Manual Call Point with Isolator

XP95 Manual Call Point



A seven-segment DIL switch enables the addressing of each call point at commissioning stage. When operated, the manual call point interrupts the polling cycle for a fast response. Bi-coloured LEDs indicate isolate and normal conditions.

'Plug and Play' terminal connections for fast wiring

Continuity link for wiring test before commissioning

Reports an alarm in under 0.2 seconds

Resettable element

55100-905
XP95 Manual Call Point

55100-908
XP95 Manual Call Point with Isolator

Waterproof Manual Call Point



The Waterproof Manual Call Point has been designed for use outdoors and in places where moisture can occur. A seven-segment DIL switch enables addressing of each call point at commissioning stage. When operated, the manual call point interrupts the polling cycle for a fast response. Bi-coloured LEDs indicate isolate and normal conditions.

'Plug and Play' terminal connections for fast wiring

Continuity link for wiring test before commissioning

Reports an alarm in under 0.2 seconds

Resettable element

58100-950
Waterproof Manual Call Point

58100-951
Waterproof Manual Call Point with Isolator

58100-953
Waterproof Manual Call Point with Isolator (yellow) †

† Non-standard variants of the Manual Call Point are not EN 54-11 compliant and therefore cannot be used to signal fire.