





Conventional Sounder Base

Description

In Fire and Security system the sounder is the most effective device for alerting personnel to evacuate the area. In the buildings such as hotels where thick doors and walls prevent external sound penetration, the use of a combined detector base with buit-in sounder present a cost effective solution. The GST C-9402 is a non-addressable sounder base on which can mounted a conventional detector to provide the dual function of detection and alarm device or it can be used as a single sounder.

Technical Specifications

- Operating voltage: 24Vdc (16Vdc to 28Vdc) polarized
- Operating Current: 15mA
- Operating temperature: -10°C to + 50°C
- Relative humidity: 95%
- Sound Output: 85dB @ 1metre
- Pre-alarm: Intermittent (0.5s on 1s off)
- Fire Alarm: Continuous (0.4s on 0.3s off)
- Application: Indoor use, IP 31
- Material and colour: ABS, white (RAL 9016)
- Wiring: 1 pair polarized
- Dimensions: diameter 10cm; height: 3.5cm (w/o cover), 4.5cm (w/ cover)


Features and Benefits

C-9402

- High sound level
- Low power consumption
- Can be used as a detector base
- Wall or ceiling mounting. Easy installation and connection.

Sounder Installation


The sounder base should be installed in compliance with all local codes or NFPA 72 National Fire Alarm Code, NFPA 70 National Electrical Code, BS5389 and EN54. It is install onto a standard one gang electrical box with a mounting hole that has 6.5cm spacing.



Wiring and Connection

Connect the wires to the required terminal according to the wiring diagram. The 5,6 is for 24VDC power supply, note the polarity 5 is positive and 6 is negative. The cable must be fire rated type and the size depends on the wiring distance. Minimum size gauge 1.0mm²(18 AWG).

POWER SUPPLY/SOUNDER OUTPUT



Selection of Compatible Control Panel

Compatible with all GST Conventional panel and GST Intelligent Fire Alarm Panels using sounder output and Intelligent Sounder Driver Module

Ordering Information



Part Number: C-9402

Description: Conventional Sounder Base

Weight / Kg.: 0.120 Pack Qty. per Box: 100

MANUFACTURED IN ACCORDANCE WITH

