

Smoke Alarm S-9102



Features and Benefits

1. Self contain Optical Smoke detector and alarm sounder
2. With test and reset button
3. 9v operated
4. Low battery indication
5. Battery removable will inhabit cover from closing (as per UL standard)
6. Easy installation
7. LED indicator for 360° vision
8. Connection port to link up to 30 detectors in a single network
9. Output to interface with other security equipment

Description

S-9102 Smoke Alarm is designed for domestic usage such as a house, villa and apartment, etc. Built with high-quality components and advanced technology, the alarm has an excellently stable performance and low power consumption. A 9V battery will operate up to one year. It can be easily installed, no commission required.

Utilize internal buzzer to provide a loud local alarm. By using the output terminal, the alarm can be linked to other alarms in a common alarm network (up to 30 alarms) or can be interfaced to other systems.

Technical Specifications

- Approval: CE
- Power Supply: PP3 (H6F22) DC9V battery
- Indicator: Red flashes in every 50 seconds in normal condition.
- Output Interface: Available for optional use
- Network Output: Maximum 30 alarm in one system, available for optional use.
- Photoelectric Output: 5mA /30VDC, Optional
- Sound level : 80dB
- Detection Area: 40m2
- Operating Environment:
- Temperature: -10 ~ +50
- Relative Humidity: 95%
- Dimension: 140 x 54mm(D x H, with base)
- Material and Color: ABS white
- Weight: 235g
- Mounting Hole Distance: 50mm~108mm

Detector Installation and Wiring

The Smoke Alarm should be installed in compliance with all local codes having a jurisdiction in your area or NFPA 72 National Fire Alarm Code, NFPA 70 National Electrical Code, BS 5389 and EN54. For information about installation refers to manual.

Ordering Information:

Part No	Description	Weight /Kg	Pack Qty per Box
S-9102	Smoke Alarm	0.300	30

MANUFACTURED IN ACCORDANCE WITH



Note: Specifications are subject to change without notice.

